

# E-17



▶ FEATURES

- Exceptionally elegant exterior
- Stylish rear side design
- Swift 3ms response time
- High 300 brightness
- Crisp 800:1 contrast ratio
- NeoV Optical Glass™
- Dual digital and analog inputs\*
- Built-in speakers with headphone jack
- Auto-adjustment for optimal settings
- Intuitive OSD with key lock function
- Kensington® security socket
- VESA standard wall mount

▶ SPECIFICATION

|                     |  |  |
|---------------------|--|--|
| Panel               | <b>Panel Type</b>                      | TFT LCD  |
|                     | <b>Panel Size</b>                      | 17.0" (432mm)  |
|                     | <b>Max. Resolution</b>                 | SXGA 1280 x 1024   |
|                     | <b>Pixel Pitch</b>                     | 0.264mm  |
|                     | <b>Brightness</b>                      | 300cd/m <sup>2</sup> (Typical)                                 |
|                     | <b>Contrast Ratio</b>                  | 800:1 (Typical)  |
|                     | <b>Surface Treatments</b>              | Hard Coating (3H), Anti-glare Treatment                        |
|                     | <b>Viewing Angle (H/V)</b>             | 160°/160° (Typical)  |
|                     | <b>Display Color</b>                   | 16.7M  |
|                     | <b>Response Time</b>                   | 3ms (GTG)  |
| Input               | <b>Frequency (H/V)</b>                 | H: 24kHz - 80kHz<br>V: 56Hz - 75Hz                             |
|                     | <b>Max. Pixel Clock</b>                | 135MHz   |
| Input               | <b>Life Time</b>                       | 50,000hrs (Minimum)  |
|                     | <b>Analog</b>                          | 15-Pin D-Sub   |
| Audio               | <b>Digital*</b>                        | 29-Pin DVI-D   |
|                     | <b>Audio In</b>                        | 3.5mm Audio Line-in  |
| Audio               | <b>Audio Out</b>                       | 3.5mm Headphone Jack   |
|                     | <b>Speaker</b>                         | 1W x 2   |
| Connector           | <b>Power</b>                           | 3-Pin AC Plug  |
| NeoV Optical Glass  | <b>Thickness</b>                       | 3.0mm (0.18")  |
|                     | <b>Reflection Rate</b>                 | <1%  |
|                     | <b>Transmission Rate</b>               | >96%   |
|                     | <b>Hardness</b>                        | >6H (MOH's Rating)   |
| Tilt                | <b>Tilt</b>                            | +5° ~ +25°   |
| Mounting            | <b>VESA FPMPMI</b>                     | Yes (100mm)  |
| Regulation Approval | <b>Certifications &amp; Compliance</b> | UL/CUL, TUV/BAURT, NORDIC, CB, FCC, CE, BSMI, GOST, WEEE, RoHS |
|                     | <b>VESA</b>                            | DDC 1/2B, DPMS   |
| Power               | <b>Power AC</b>                        | 100 - 240V, 50 - 60Hz  |
|                     | <b>Consumption</b>                     | <48W (On)<br><2W (Stand-by)<br><1W (Off)                       |
| Dimensions          | <b>Net (W x H x D)</b>                 | 400 x 390 x 171mm<br>(15.8" x 15.4" x 6.7")                    |
|                     | <b>Packing (W x H x D)</b>             | 555 x 580 x 171mm<br>(21.9" x 22.8" x 6.7")                    |
| Weight              | <b>Net Weight</b>                      | 6.2Kg (13.6 lbs)   |
|                     | <b>Gross Weight</b>                    | 8.0Kg (17.7 lbs)   |

\*DVI input is an optional function

All specifications are subject to change without prior notice



[www.agneovo.com](http://www.agneovo.com)

Copyright © 2007 AG Neovo. All rights reserved.  
The name AG Neovo is a trademark of Associated Industries China, Inc.  
All other trademarks are the property of their respective owners.